

KEY BENEFITS

- > Provides freedom of movement with no protruding parts or cumbersome wires or cables
- > Rugged construction and noise cancellation technologies support clear audio in harsh environmental conditions
- > Real-time Push-To-Talk with

GENERAL SPECIFICATIONS	
Dimensions (H x W x D):	3.5 x 3.0 x 0.8 in (88 x 77 x 21 mm)
Approximate Weight:	4.4 oz (125g)
Operating Temperature Range:	-22 to +140°F (-30 to +60°C)
Storage Temperature Range:	-40 to +104°F (-40 to +85°C)
Charging Temperature Range:	+32 to +104°F (0 to +40°C)
AC Charge Range:	100-240V, 50-60 Hz
Drop Performance:	2 meters
PTT Operations:	200 thousand nominal

MICROPHONE SPECIFICATIONS	
Type:	Electret, Omni-directional
Maximum Acoustic Input before Significant Distortion:	120 dB SPL
Frequency Range:	300 to 3600 Hz

SPEAKER SPECIFICATIONS	
Type:	40 mm Moving Coil, 1 Wrms, 2 Wpk, 8 Ohm
Maximum Acoustic Output at 50 cm:	89 dBA (A2DP mode, multitone)
Frequency Range:	300 to 3600 Hz