BATTLEFIELD AWARENESS AND TARGETING SYSTEM-EMBEDDED 1500

Embeddable, Single-Channel Link 16 Comms for SWaP-Constrained Systems

With L3Harris Battle eld Awareness and Targeting System-Embedded 1500 (BATS-E 1500) Size, Weight and Power (SWaP)-constrained systems, including targeting pods and network enabled weapons, are now accounted for in the Common Operational Picture. This 360-degree visibility provides all Link 16 network participants with the ability to see, relay and share situational awareness data and allows for more accurate tracking, identi cation and engagement so controllers now have a clear view of the battlespace.

PRODUCT DESCRIPTION

Designed for missions with longer transmission ranges, the low SWaP BATS-E 1500 is optimized for embedded applications. Controllers now have the ability to send target updates while in flight for secure, reliable weapons delivery, so as to signi cantly decrease the time in high-threat environments.

The BATS-E 1500's Enhanced Throughput (ET) mode boosts Link 16's protected data rate of 115 Kbps to over 1.1 Mbps. When combined with the Concurrent Multiple Reception (CMR) capability, the BATS-E 1500 is the rst Link 16 radio capable of data rates in excess of 2 Mbps. The Concurrent Multinet (CMN) and Concurrent Contention Receive (CCR) features have also been implemented in the latest version of the BATS-E 1500. With Link 16 Cryptographic Modernization, the BATS-E also implements the latest high assurance algorithms using a eld proven programmable crypto engine to