

MIDS-LVT(1) RU MOBILE SYSTEM

MIDS Support Equipment

The L3Harris Multifunctional I (MIDS)-Low Volume Terminal (MIDS)-LVT(1) is an all-in-one, transportable case variant. Outfitted with all of the features needed to operate a MIDS-LVT(1) terminal, it includes a rugged computer and a rugged, easy-to-operate web interface.

- > Terminal Power
- > Crypto Hold
- > LTTI
- > IFF Emergency
- > Fail Decode
- > Platform (IOIDENT) Configuration
- > 1553 Address (RTAD)
- > Crypto Broize

The MIC offers a standard fill device for crypto with standard fill device.

The mobile system also includes a rugged interface unit that provides voice (receive and transmit). It has been tuned to enhance audio quality for mobile phones and handsets and is also controlled by the MIC.

PERFORMANCE

- > Input Power: 120 VAC 60 Hz, 20 amp (IEC C20)
230/240 VAC 50 Hz, 10 amp (IEC C14)
- > Dimensions: 18.1" (w) x 22.5" (h) x 34.5" (d)
- > Weight (Approximate): 200 lbs

STANDARD CABLES

- > W2, W3 and W7: Link 16 Voice/Data/Control
- > W4: Crypto
- > W10 and W11: Link 16 RF Cables
- > RPS 280VDC: Power Cable

STANDARD ACCESSORIES

- > 120 VAC Input Power Cable, NEMA 5-20P to IEC C19 (specify if international cables are required)
- > W1, W12 & W56 – LVT-1 RPS TO MT Cables
- > BNC to BNC 1PPS Jumper Cable
- > H-250 Handset
- > User Guide

PARTS DESCRIPTION

- > MIDS-LVT(1) Ruggedized Mobile Rack