


LMR TRANSMITTER

Feature/Bandwidth	VHF	UHF	700/800 MHz	900 MHz
Frequency Range (MHz)	136-174	378-522	768-776, 798-806, 806-816, 851-861	896-902, 935-944
Channel Spacing (kHz)	136-174	378-522	763-776, 793-806, 806-825, 851-870	896-902, 935-944
Rated RF Power (W)	1-6	1-5	0.5-3	0.5-3.5
Frequency Stability (-30 to +60 C)	±1.0 ppm	±1.0 ppm	±1.0 ppm	±1.0 ppm
Modulation (MHz)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)
Adjacent Channel Rejection (dB)	+1/-3	+1/-3	+1/-3	+1/-3
Spurious Rejection (dBc)	-80 (FCC Part 90)	-80 (FCC Part 90)	-80 (FCC Part 90)	-80 (FCC Part 90)
FMH Modulation Reciprocity (dB): @ 25 kHz @ 12.5 kHz	70 47	60 47	55 45	55 45
Adjacent Channel Interference (%)	<1.25	<1.25	<1.25	<1.25
Percent Modulation (25 MHz)	1.0	1.0	1.0	1.0
Percent Adjacent Channel Interference (25 MHz)	>71	>71	>71	>70



ACCESSORIES				
Speaker Microphones				
L3Harris offers a versatile line of speaker microphones for your mobile communications. In addition, a premium leather holster is available for attaching to a belt or wearing with the premium leather shoulder strap.				
XL Extreme Speaker Mic	Standard Mic	REVO NC2 Speaker Mic	Advanced Bluetooth Speaker Mic	500 Fire-Rated Speaker Mic
Chargers				
The XL 150P comes bundled with a XL Single-Bay+ Charger.				
XL Single-Bay+ Charger	Multi-bay Charger*	Vehicular Charger*		
Add-on Accessories Available				
Bluetooth speaker microphones, Bluetooth cover pieces, standard speaker microphones, Lithium Ion battery, PC programming software and cables, other subminiature surveillance accessories, and antennas.				